STAPPERT

QUALITY EX STOCK

Summary of available products



EXPORT DIVISION

- Bars
- Angles
- Special sections
- Pipes and tubes
- Hollow bars

INOX INTELLIGENCE.

STAPPERT – THE BRAND FOR STAINLESS STEELS.

STAPPERT is one of the leading distributors of long products and fittings made of stainless, highly corrosion and heat resistant steel.

We have the stainless steel that fits your requirements perfectly and supply it in a range of standard and tailor-made solutions that is unique in stainless steel business. Furthermore you can expect first-class service from us in every respect.

Tailored to provide you the greatest possible benefit from start to finish: in addition to the enormous variety of products and reliable delivery – for which the name STAPPERT stands for – you can also rely on our ongoing commitment to progress, development and the further optimization of our services. This is what we mean by INOX INTELLIGENCE.

We – the STAPPERT team – see ourselves as competent contact persons for the interests of different branches of industry. From mechanical engineering to energy and environmental technology to the food industry, we are at home in all sectors and have built up our reputation as a competent partner over decades.

STAPPERT's emphasis is not only on a wide range of stainless, highly corrosion and heat resistant steels, but also on good accessibility and location-independent support. We are always on hand, wherever you are. Your reliable global partner with comprehensive coverage of your needs and short delivery times.

BARS | COLD-FORMED

grade	AISI/ UNS	DIN EN 10278 h9	DIN EN 10278 h8	DIN EN 10278 h6	polished	DIN EN 10278	DIN EN 10278	DIN EN 10278		equal	key steel	key steel
1.4021	420	4 - 100	-	-	-	-	-	-	-	-	-	-
1.4034	420	5 - 90	-	-	-	-	-	-	-	-	-	-
1.4057	431	5 - 100	-	-	-	-	11 - 41	-	-	-	-	-
1.4104	430 F	3 - 100	-	-	-	6 - 60	5 - 55	-	-	-	-	-
1.4112	440 B	5 - 80	-	-	-	-	-	-	-	-	-	-
1.4122		5 - 100	-	-	-	-	-	-	-	-	-	-
1.4301 1.4307	304 304L	2 - 100	6 - 60	10 - 50	8 - 20	4 - 100	7 - 75	8 × 4 - 160 × 10	-	10 × 10 × 2 - 60 × 60 × 6	-	-
1.4301 Ugima	304 Ugima	8 - 90	-	-	-	-	27 - 41	-	-	-	-	-
1.4305	303	2 - 100	10 - 30	-	8 - 20	5 - 100	5 - 65	20 × 5 - 120 × 20	-	-	-	-
1.4305 Ugima	303 Ugima	6 - 90	-	-	-	-	-	-	-	-	-	-
1.4401 1.4404	316 316L	3 - 100	-	-	-	10 - 60	6 - 75	15 × 3 - 100 × 20	10 × 3,5 - 50 × 25	-	-	-
1.4404 Ugima	316 L Ugima	8 - 60	-	-	-	-	-	-	-	-	-	-
1.4418		12 - 22	-	-	-	-	-	-	-	-	-	-
1.4435	316 L	4 - 80	-	-	-	-	13 - 41	-	-	-	-	-
1.4435 Ugima	316 L Ugima	4 - 80	-	-	-	-	-	-	-	-	-	-
1.4460	S 32900	16 - 80	-	-	-	-	-	-	-	-	-	-
1.4462	S 31803	6 - 80	-	-	-	-	-	-	-	-	-	-
1.4539	904 L	6 - 20	-	-	-	-	19 - 30	-	-	-	-	-
1.4541	321	3 - 100	-	-	-	-	13 - 65	-	-	-	-	-
1.4542	630	8 - 40	-	-	-	-	-	-	-	-	-	-
1.4571	316 Ti	2 - 100	-	-	-	4 - 100	6 - 70	10 × 3 - 120 × 10	-	-	5 × 3 - 40 × 22	3 - 6
1.4571 Ugima	316 Ti Ugima	8 - 60	-	-	-	-	22 - 55	-	-	-	-	-
1.4828	309	6 - 20	-	-	-	-	-	-	-	-	-	-
1.4841	314	3 - 20	-	-	-	-	13 - 36	-	-	-	-	-
1.4845	310 S	6 - 20	-	-	-	-	-	-	-	-	-	-
1.4923		10 - 20	-	-	-	-	-	-	-	-	-	-

BARS | HOT-FORMED

grade	AISI/ UNS	DIN EN 10060 ●	DIN EN 10059 ■	DIN EN 10058 ▬	slit ▬	equal L	equal polished L	unequal L	T	I	U
	XM 19 * Nitronic 50 ©	30 - 200	-	-	-	-	-	-	-	-	-
1.4006	410	30 - 400	-	-	-	-	-	-	-	-	-
1.4021	420	18 - 550	-	-	-	-	-	-	-	-	-
1.4028	420 F	30 - 200	-	-	-	-	-	-	-	-	-
1.4034	420	30 - 325	-	-	-	-	-	-	-	-	-
1.4057	431	20 - 500	40 - 100	30 × 20 - 100 × 30	-	-	-	-	-	-	-
1.4104	430 F	34 - 400	80	-	-	-	-	-	-	-	-
1.4112	440 B	25 - 400	-	-	-	-	-	-	-	-	-
1.4122		22 - 525	-	-	-	-	-	-	-	-	-
1.4125	440 C	20 - 225	-	-	-	-	-	-	-	-	-
1.4301 1.4307	304 304L	20 - 575	10 - 200	10 × 5 - 200 × 40	10 × 3 - 300 × 12	15 × 15 × 2 - 180 × 180 × 20	20 × 20 × 3 - 60 × 60 × 6	20 × 10 × 3 - 200 × 100 × 12	T 20 - 120 TB 30 - 60	IPE 80 - 240 IPB 100 - 200	U 20 - 200
1.4301 Ugima	304 Ugima	40 - 120	-	-	-	-	-	-	-	-	-
1.4305	303	30 - 500	40 - 150	-	-	-	-	-	-	-	-
1.4305 UGIMA	303 UGIMA	40 - 75	-	-	-	-	-	-	-	-	-
1.4306	304 L	35 - 200	-	-	-	-	-	-	-	-	-
1.4313	CA6-NM	20 - 500	-	-	-	-	-	-	-	-	-
1.4401 1.4404	316 316L	20 - 625	10 - 150	20 × 5 - 200 × 40	10 × 3 - 200 × 10	20 × 20 × 3 - 100 × 100 × 10	-	-	-	-	-
1.4404 Ugima	316 L Ugima	30 - 120	-	-	-	-	-	-	-	-	-
1.4410	S 32750	16 - 425	-	-	-	-	-	-	-	-	-
1.4418		25 - 350	-	-	-	-	-	-	-	-	-
1.4435	316 L	30 - 400	30 - 80	-	-	-	-	-	-	-	-
1.4439	317 LMN	20 - 210	-	-	-	-	-	-	-	-	-
1.4460	S 32900	31 - 255	-	-	-	-	-	-	-	-	-
1.4462	S 31803	20- 500	20 - 60	30 × 5 - 100 × 20	-	-	-	-	-	-	-
1.4501	S 32760	25 - 500	-	-	-	-	-	-	-	-	-
1.4529	N 08926	16 - 200	-	-	-	-	-	-	-	-	-
1.4539	904 L	22 - 400	15 - 50	-	-	-	-	-	-	-	-
1.4541	321	20 - 525	25 - 150	20 × 5 - 150 × 20	20 × 3 - 100 × 12	20 × 20 × 3 - 100 × 100 × 10	-	-	-	-	-
1.4542	630	30 - 400	-	-	-	-	-	-	-	-	-
1.4542* H1150D	**630/H1150D 17-4PH**	**50 - 200**	-	-	-	-	-	-	-	-	-
1.4547	S31254	20 - 225	-	-	-	-	-	-	-	-	-
1.4550	347	30 - 200	-	-	-	-	-	-	-	-	-
1.4571	316 Ti	20 - 625	15 - 200	12 × 6 - 150 × 50	10 × 3 - 250 × 15	20 × 20 × 3 - 150 × 150 × 15	-	30 × 20 × 3 - 200 × 100 × 13	T 40 - 120	IPE 80 - 160 IPB 100 - 180	U 40 - 200
1.4571 Ugima	316 Ti Ugima	45 - 125	-	-	-	-	-	-	-	-	-
1.4762	446	16 - 120	-	-	-	-	-	-	-	-	-
1.4828	309	22 - 350	-	20 × 8 - 100 × 20	-	-	-	-	-	-	-
1.4835	S30815	30 - 200	-	-	-	-	-	-	-	-	-
1.4841	314	20 - 300	10 - 80	15 × 5 - 120 × 10	-	-	-	-	-	-	-
1.4845	310 S	30 - 400	-	-	-	-	-	-	-	-	-
1.4876	800 H	20 - 100	-	-	-	-	-	-	-	-	-
1.4878	321 H	20 - 525	25 - 150	20 × 5 - 150 × 20	-	-	-	-	-	-	-
1.4923		25 - 220	-	-	-	-	-	-	-	-	-
	304 H	30 - 150				-	-	-	-	-	-
1.4980	660 *	30 - 100									

*new

TUBES AND PIPES | SEAMLESS

grade	AISI/ UNS	seamless	hydraulic tubes EN 10305/1
1.4301 1.4307	304 304L	4.0 × 1.0 - 323.9 × 12.7*	4.0 × 1.0 - 42.0 × 3.0
1.4306	304 L	12.0 × 1.5 - 88.9 × 3.05	-
1.4401 1.4404	316 316L	6.0 × 0.5 - 323.9×12.7*	6.0 x 1.0 - 18.0 x 1.0
1.4410	F53 UNS S32750	21.34 × 2.77 - 114.3 × 6.02	-
1.4462	S 31803	13.72 × 2.24 - 219.1 × 8.18	-
1.4501	S 32760	21.34 × 2.77 -88.9 x 5.49	-
1.4539	904 L	17.14 × 2.31 - 219.1 × 12.7	-
1.4541	321	6.0 × 1.0 - 219.1 × 12.7	6.0 × 1.0 - 35.0 × 2.5
1.4571	316 Ti	4.0 × 0.5 - 323.9 × 12.7*	4.0 × 1.0 - 42.0 × 3.0
1.4841	314	6.0 × 1.0 - 168.3 × 4.5	-
1.4845	310 S	13.72 × 2.24 - 219.1 × 12.7	-
1.4878	321 H	6.0 × 1.0 - 219.1 × 12.7	-

*new

TUBES AND PIPES | WELDED

grade	AISI/ UNS	not annealed	annealed	annealed polished	dairy tubes
1.4301 1.4307	304 304L	6.0 × 1.0 - 812.8 × 4.0	6.0 × 1.0 - 609.6 × 9.53	25.0 × 2.0 - 42.4 × 2.6	18.0 × 1.5 - 204.0 × 2.0
1.4404	316 L	6.0 × 1.0 - 812.8 × 4.0	6.0 × 1.0 - 609.6 × 9.53	21.3 × 2.0 - 33.7 × 2.0	18.0 × 1.5 - 204 × 2.0
1.4541	321	15.0 × 1.5 - 355.6 × 4.0	12.0 × 1.0 - 114.3 × 4.0	-	-
1.4571	316 Ti	10.0 × 1.0 - 609.60 × 4.0	6.0 × 1.0 - 114.3 × 5.0	-	-

CONSTRUCTION TUBES

grade	AISI/ UNS	round	round polished	square	square polished	rectangular	rectangular geschliffen
1.4301	304	12 × 1.0 - 139.7 × 4.0	12.0 × 1.0 - 114.3 x 3.0	10 × 10 × 1.0 - 200 × 200 × 8.0	15 × 15 × 1.5 - 120 × 120 × 3.0	20 × 10 × 1.5 - 200 × 150 × 5.0	20 × 10 × 1.5 - 150 × 50 × 3.0
1.4404	316 L	-	40.0 × 2.0 - 60.3 × 3.0	15 × 15 × 1.5 - 200 × 200 × 5.0	-	30 × 20 × 2.0 - 200 × 100 × 6.0	-
1.4571	316 Ti	-	-	15 × 15 × 1.5 - 100 × 100 × 5.0	-	20 × 10 × 1.5 - 80 × 60 × 4.0	-

Higher quality surface finishes above 240 grit are available on request for many grades of material.

HOLLOW BARS

grade	AISI/ UNS	seamless
1.4301 1.4307	304 304L	32 × 16 - 400 × 300
1.4401 1.4404	316 316 L	32 × 16 - 420 × 300
1.4462	S 31803	50 × 25 - 250 × 200
1.4541	321	36 × 20 - 250 × 200
1.4571	316 Ti	32 × 16 - 250 × 200
1.4878	321 H	36× 20 - 250 × 200

FLANGES

grade	1.4301/1.4307	1.4401/1.4404
AISI/UNS	304/304 L	316/316 L
Welding neck flanges according to EN	PN 06: DN 15/21.3 - DN 600/609.6 PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/54 - DN 600/609.6 PN 25: DN 200/219.1 - DN 600/609.9 PN 40: DN 10/17.2 - DN 300/323.9	PN 06: DN 15/21.3 - DN 600/609.6 PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/54 - DN 600/609.6 PN 25: DN 200/219.1 - DN 600/609.9 PN 40: DN 10/17.2 - DN 300/323.9
Welding neck flanges according to EN with reduced S-size	-	-
Welding neck flanges according to DIN	PN16: DN 15/21.3 - DN 32/42.4	-
Welding neck flanges according to ASTM	150#: 1/2“ SCH10S - 24“ SCH40S 300#: 1/2“ SCH40S - 16“ SCH80S 600#: 1/2“ SCH80S - 10“ SCH80S	150#: 1/2“ SCH10S - 24“ SCH40S 300#: 1/2“ SCH40S - 16“ SCH80S 600#: 1/2“ SCH80S - 10“ SCH80S
Flanges for automatic welding according to EN	-	-
Flanges for automatic welding according to DIN	-	-
BSP threaded flanges according to EN	PN 16: DN 50/60.3 - DN 100/114.3 PN 40: DN 10/17.2 - DN 40/48.3	PN 16: DN 50/60.3 - DN 100/114.3 PN 40: DN 10/17.2 - DN 40/48.3
Threaded flanges according to DIN	-	-
NPT threaded flanges according to ASTM	150#: 1/2“/21.3 - 2“/60.5 300#: 1/2“/21.3 - 2“/60.5	150#: 1/2“/21.3 - 3“/88.9 300#: 1/2“/21.3 - 2“/60.5
Slip-on flanges according to EN	PN 06: DN 15/21.3 - DN 600/609.6 PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/50.8 - DN 400/406.4 PN 40: DN 10/17.2 - DN 40/48.3	PN 06: DN 15/21.3 - DN 600/609.6 PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/50.8 - DN 400/406.4 PN 40: DN 10/17.2 - DN 40/48.3
Slip-on flanges according to DIN	-	-
Slip-on flanges according to DIN with reduced thickness	PN 10: DN 50/60.3 - DN 1000/1016	PN 10: DN 300/323.9 - DN 1000/1016
Slip-on flanges according to EN with reduced thickness	PN 10: DN 15/21.3 - DN 600/610	-
Slip-on flanges according to ASTM	150#: 1/2“/21.3 - 24“/609.6 300#: 1/2“/21.3 - 12“/323.9	150#: 1/2“/21.3 - 24“/609.6 300#: 1/2“/21.3 - 12“/323.9
Lap-joint flanges according to EN	PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/50.8 - DN 200/219.1 PN 40: DN 10/17.2 - DN 40/48.3	PN 10: DN 200/204 - DN 800/812.8 PN 16: DN 50/50.8 - DN 200/219.1 PN 40: DN 10/17.2 - DN 200/219.1
Lap-joint flanges according to DIN	-	-
Lap-joint flanges according to DIN with reduced thickness	PN 10: DN 50/60.3 - DN 600/609.6	PN 10: DN 300/323.9 - DN 600/609.6
Lap-joint flanges according to EN with reduced thickness	PN 10: DN 15/21.3 - DN 600/609.6	-
Lap-joint flanges according to ASTM	150#: 1/2“/21.3 - 24“/609.6	150#: 1/2“/21.3 - 24“/609.6
Blind flanges according to EN	PN 06: DN 50 - DN 600 PN 10: DN 200 - DN 800 PN 16: DN 50 - DN 600 PN 40: DN 10 - DN 150	PN 06: DN 50 - DN 600 PN 10: DN 200 - DN 800 PN 16: DN 50 - DN 600 PN 40: DN 10 - DN 150
Blind flanges according to DIN	-	-
Blind flanges according to DIN with reduced thickness	PN 10: DN 200 - DN 600 PN 16: DN 100 - DN 150	PN 10: DN 300 - DN 600
Blind flanges according to EN with reduced thickness	PN 10: DN 15 - DN 500	-
Blind flanges according to ASTM	150#: 1/2“/21.3 - 24“/609.6 300#: 1/2“/21.3 - 16“/406.4 600#: 1/2“/21.3 - 8“/219.2	150#: 1/2“/21.3 - 24“/609.6 300#: 1/2“/21.3 - 16“/406.4 600#: 1/2“/21.3 - 8“/219.2
Socket-weld flanges according to ASTM	-	150#: 1/2“/21.3 - 4“/114.3
Pressed flanges	PN 10: DN 15 - DN 300	PN 10: DN 15 - DN 300

FLANGES

grade	1.4541	1.4571	Aluminium
AISI/UNS	321	316 Ti	
Welding neck flanges according to EN	PN 10: DN 200/219.1 - DN 400/406.4 PN 16: DN 50/60.3 - DN 400/406.4 PN 40: DN 15/21.3 - DN 80/88.9	PN 10: DN 200/204 - DN 600/609.6 PN 16: DN 50/54 - DN 500/508.0 PN 40: DN 10/17.2 - DN 200/219.1	-
Welding neck flanges according to EN with reduced S-size	-	PN10: DN 200/219.1 - DN 250/273.0	-
Welding neck flanges according to DIN	PN16: DN 10/17.2 - DN 40/48.3	PN16: DN 10/17.2 - DN 150/159.0	-
Welding neck flanges according to ASTM	-	-	-
Flanges for automatic welding according to EN	-	PN16: DN 15/21.3 - DN 200/219.1 PN40: DN 15/21.3 - DN 150/168.3	-
Flanges for automatic welding according to DIN	-	PN16: DN 15/21.3 - DN 50/60.3	-
BSP threaded flanges according to EN	-	PN 16: DN 50/60.3 - DN 80/88.9 PN 40: DN 10/17.2 - DN 40/48.3	-
Threaded flanges according to DIN	-	PN 10: DN 15/21.3 - DN 100/114.3 PN 16: DN 15/21.3 - DN 100/114.3	-
NPT threaded flanges according to ASTM	-	-	-
Slip-on flanges according to EN	PN 10: DN 250/273 - DN 500/508 PN 16: DN 80/88.9 - DN 125/139.7	PN 10: DN 200/206 - DN 800* PN 16: DN 50/54 - DN 300/323.9 PN 40: DN 15/21.3 - DN 40/48.3	-
Slip-on flanges according to DIN	PN 10: DN 15/21.3 - DN 200/219.1	PN 10: DN 15/21.3 - DN 200/219.1	-
Slip-on flanges according to DIN with reduced thickness	-	PN 10: DN 50/60.3 - DN 500/508 PN 16: DN 65/76.1 - DN 600/609.6	-
Slip-on flanges according to EN with reduced thickness	PN 10: DN 15/21.3 - DN 300/323.9	PN 10: DN 15/21.3 - DN 800*	-
Slip-on flanges according to ASTM	-	-	-
Lap-joint flanges according to EN	PN 10: DN 200/219.1 - DN 500/508 PN 16: DN 50/60.3 - DN 150/168.3 PN 40: DN 15/21.3 - DN 40/48.3	PN 10: DN 200/219.1 - DN 600/609.6 PN 16: DN 50/60.3 - DN 250/273 PN 40: DN 15/21.3 - DN 40/48.3	-
Lap-joint flanges according to DIN	PN 10: DN 10/17.2 - DN 250/273	PN 10: DN 10/17.2 - DN 250/273	PN 10: DN 15/21.3 - DN 300/323.9
Lap-joint flanges according to DIN with reduced thickness	-	PN 10: DN 50/60.3 - DN 600/609.6	-
Lap-joint flanges according to EN with reduced thickness	PN 10: DN 15/21.3 - DN 300/323.9	PN 10: DN 15/21.3 - DN 300/323.9	-
Lap-joint flanges according to ASTM	-	-	-
Blind flanges according to EN	PN 10: DN 200 - DN 300 PN 16: DN 50 - DN 400 PN 40: DN 15 - DN 50	PN 10: DN 200 - DN 500 PN 16: DN 50 - DN 300 PN 40: DN 10 - DN 200	-
Blind flanges according to DIN	PN 16: DN 15 - DN 40	PN 16: DN 10 - DN 40	PN 10: DN 15 - DN 300
Blind flanges according to DIN with reduced thickness	-	PN 10: DN 200 - DN 600 PN 16: DN 100 - DN 150	-
Blind flanges according to EN with reduced thickness	PN 10: DN 25 - DN 300	PN 10: DN 20 - DN 300	-
Blind flanges according to ASTM	-	-	-
Socket-weld flanges according to ASTM	-	-	-
Pressed flanges	-	-	-

*new

BUTT WELDED FITTINGS

grade	1.4301/1.4307	1.4401/1.4404	1.4432	1.4462	1.4539	1.4541	1.4571
AISI/UNS	304/304 L	316/316 L	316 L	S 31803	904 L	321	316 Ti
Elbow 90° seamless according to EN	-	-	-	-	-	12.0 x 1.5 - 168.3 x 4.5	12.0 x 1.5 - 168.3 x 4.5
Elbow 90° seamless according to ASTM	21.34 x 2.11 - 323.9 x 12.7	21.34 x 2.11 - 323.9 x 12.7	-	21.34 x 2.11 - 219.10 x 8.18	21.34 x 2.11 - 168.3 x 7.11	-	-
Elbow 90° welded according to EN	12.0 x 1.5 - 812.8 x 4.0	12.0 x 1.5 - 813.0 x 4.0	26.9 x 2.0 - 608.0 x 4.0	-	-	17.2 x 1.6 - 406.4 x 3.0	17.2 x 1.6 - 609.6 x 4.0
Elbow 90° welded according to ASTM	21.34 x 2.11 - 609.6 x 9.53	21.34 x 2.11 - 610.0 x 9.53	-	-	-	-	-
Elbow 180° seamless according to ASTM	21.34 x 2.11 - 114.3 x 3.05	21.34 x 2.11 - 114.3 x 3.05	-	-	-	-	-
Elbow 45°seamless according to ASTM	21.34 x 2.11 - 219.08 x 8.18	21.34 x 2.11 - 219.1 x 8.18	-	-	-	-	-
Elbow 45° welded according to ASTM	168.28 x 3.4 - 406.4 x 9.53	168.28 x 3.4 - 406.4 x 9.53	-	-	-	-	-
Tee seamless according to EN	-	-	-	-	-	21.3 x 2.0 - 60.3 x 2.0	17.2 x 2.3 - 114.3 x 3.6
Tee welded according to EN	21.3 x 2.0 - 219.1 x 3.0	13.5 x 1.6 - 219.1 x 3.0	21.3 x 2.0 - 156.0 x 3.0	-	-	21.3 x 2.0 - 219.1 x 3.0	21.3 x 2.0 - 323.9 x 3.0
Tee welded according to EN with short branch	21.3 x 2.0 - 609.6 x 2.9	17.2 x 1.6 - 610.0 x 2.9	-	-	-	-	-
Tee seamless according to ASTM	21.34 x 2.11 - 323.85 x 12.7	21.34 x 2.11 - 323.9 x 12.7	-	-	-	-	-
Tee welded according to ASTM	21.34 x 2.11 - 406.4 x 9.53	21.34 x 2.11 - 610.0 x 9.53	-	-	-	-	-
Reducing tee seamless according to EN	-	-	-	-	-	33.7 x 2.6 / 21.3 x 2.0 - 60.3 x 2.9 / 21.3 x 2.0	33.7 x 2.6 / 21.3 x 2.0 - 168.3 x 4.5 / 88.8 x 3.2
Reducing tee seamless according to ASTM	26.67 x 2.11 / 21.34 x 2.11 - 323.9 x 9.53 / 273.0 x 9.27	26.67 x 2.11 / 21.34 x 2.11 - 323.9 x 9.53 / 273.0 x 9.27	-	-	-	-	-
Reducing tee welded according to EN	21.3 x 2.0 / 17.2 x 2.0 - 219.1 x 3.0 / 168.3 x 3.0	-	-	-	-	48.3 x 2.0 / 21.3 x 1.6 - 60.3 x 2.0 / 48.3 x 2.0	26.9 x 2.0 / 21.3 x 2.0 - 168.3 x 2.6 / 114.3 x 2.6
Reducing tee welded according to ASTM	-	355.6 x 4.78 / 273.0 x 4.19 - 406.4 x 9.53 / 355.6 x 9.53	-	-	-	-	-
Reducer concentric seamless according to EN	-	-	-	-	-	26.9 x 1.6 / 21.3 x 1.6 - 114.3 x 2.6 / 76.1 x 2.3	21.3 x 2.0 / 17.2 x 1.8 - 219.1 x 6.3 / 137.9 x 4.0
Reducer excentric seamless according to EN	-	-	-	-	-	-	88.9 x 3.2 / 76.1 x 2.9 - 114.3 x 3.6 / 76.1 x 2.9
Reducer concentric welded according to EN	17.2 x 2.0 / 13.5 x 2.0 - 610.0 x 4.0 / 508.0 x 4.0	21.3 x 2.0 / 13.5 x 2.0 - 610.0 x 3.0 / 508.0 x 3.0	-	-	-	26.9 x 1.6 / 17.2 x 1.6 - 273.0 x 3.0 / 219.1 x 3.0	21.3 x 2.0 / 13.5 x 1.8 - 323.9 x 3.0 / 273.0 x 3.0
Reducer excentric welded according to EN	-	21.3 x 2.0 / 17.2 x 2.0 - 323.9 x 3.0 / 273.0 x 3.0	-	-	-	-	33.7 x 2.0 / 21.3 x 2.0 - 219.1 x 2.9 / 168.3 x 2.9
Reducer concentric seamless according to ASTM	26.67 x 2.87 / 17.14 x 2.31 - 323.9 x 17.48 / 273.0 x 9.27	26.7 x 2.87 / 17.2 x 2.31 - 323.9 x 17.48 / 273.0 x 9.27	-	-	-	-	-
Reducer excentric seamless according to ASTM	26.67 x 2.11 / 21.33 x 2.11 - 323.9 x 10.31 / 168.3 x 7.11	26.67 x 2.11 / 21.33 x 2.11 - 323.9 x 9.53 / 273.0 x 9.27	-	-	-	-	-
Reducer concentric welded according to ASTM	26.9 x 2.11 / 21.3 x 2.11 - 406.4 x 9.53 / 355.6 x 9.53	26.9 x 2.11 / 21.3 x 2.11 - 610.0 x 9.53 / 508.0 x 9.53	-	-	-	-	-
Reducer excentric welded according to ASTM	219.08 x 3.76 / 114.3 x 3.05 - 323.9 x 9.53 / 273.0 x 9.27	219.1 x 3.76 / 114.3 x 3.05 - 323.9 x 9.53 / 273.0 x 9.27	-	-	-	-	-
Cap according to EN	17.2 x 2.0 - 813.0 x 4.0	17.2 x 2.0 - 610.0 x 4.0	-	-	-	-	-
Cap according to DIN	-	-	-	-	-	-	21.3 x 2.0 - 508.0 x 4.0
Cap according to ASTM	21.34 x 2.11 - 610.0 x 9.53	21.34 x 2.11 - 610.0 x 9.53	-	-	-	-	-
Stub-end according to ASTM	21.3 x 2.11 - 406.4 x 4.78	21.3 x 2.11 - 406.4 x 4.78	-	-	-	-	-
Welding collar similar to DIN	17.2 x 2.0 - 813.0 x 4.0	17.2 x 2.0 - 610.0 x 4.0	-	-	-	17.2 x 1.8 - 508.0 x 4.0	17.2 x 2.0 - 813 x 4,0*

*new

STAPPERT DEUTSCHLAND GMBH

Export
An der Strusbek 54
22926 Ahrensburg
GERMANY
T +49 4102 4741-95
export@stappert.biz

Head Office
Willstätterstraße 13
40549 Düsseldorf
GERMANY
T +49 211 5279-0
deutschland@stappert.biz

STAPPERT INTERNATIONAL

STAPPERT Česká republika spol. s r.o.
Otmarov 57
66457 Měnín
CZECH REPUBLIC
T +420 544 423 911
ceskarepublika@stappert.biz
ceskarepublika.stappert.biz

STAPPERT Deutschland GmbH
Willstätterstraße 13
40549 Düsseldorf
GERMANY
T +49 211 5279-0
deutschland@stappert.biz
deutschland.stappert.biz

STAPPERT Fleischmann GmbH
Gewerbepark B17/I/Objekt 1
2524 Teesdorf
AUSTRIA
T +43 2253 90313-0
fleischmann@stappert.biz
fleischmann.stappert.biz

STAPPERT France SAS
Rue Charlemagne 13
02200 Soissons
FRANCE
T +33 3 23 73 50 00
france@stappert.biz
france.stappert.biz

STAPPERT Intramet SA
Rue du Parc Industriel, 5
4480 Engis
BELGIUM
T +32 4 275 82 11
intramet@stappert.biz
intramet.stappert.biz

STAPPERT Magyarország Kft.
Rétifarkas utca 1.
1172 Budapest
HUNGARY
T +36 1 4342424
magyarorszag@stappert.biz
magyarorszag.stappert.biz

STAPPERT Noxon B.V.
Gerstdijk 4
5704 RG Helmond
THE NETHERLANDS
T +31 492 582111
noxon@stappert.biz
noxon.stappert.biz

STAPPERT Polska Sp. z o.o.
ul. A. Gaudiego 18
44-109 Gliwice
POLAND
T +48 32 3447300
polska@stappert.biz
polska.stappert.biz

STAPPERT Slovensko a.s.
Šimonovská 37
97271 Nováky
SLOVAKIA
T +421 46 51834-20
slovensko@stappert.biz
slovensko.stappert.biz

STAPPERT Sverige AB
Box 82
34321 Älmhult
SWEDEN
T +46 476 48550
sverige@stappert.biz
sverige.stappert.biz

STAPPERT UK Ltd.
Unit 7 Symondscliffe Way
Severn Bridge Industrial Estate
Portskewett | Caldicot NP26 5PW
GREAT BRITAIN
T +44 121 740 0175
uk@stappert.biz
uk.stappert.biz

group.stappert.biz

Status: February 2026 | This information is supplied without liability.

STAPPERT